



## USE AND OPERATING INSTRUCTIONS FOR THE VAPORTRONIC 2.0™



### **Vaportronic 2.0** *Refillable, Electronic Wall Cabinet System*

May be used free-standing  
or wall-mounted.



### WALL-MOUNTING INSTRUCTIONS

1. Position Vaportronic 2.0 on wall where unit is to be mounted & mark top of unit. Allow at least 3" clearance above unit for hinged cover to lift open.
2. Measure 1.25" down from mark & drill top mounting hole using 3/16" drill bit.
3. Insert supplied anchor into hole & insert supplied screw into anchor leaving a 1/8" protrusion.
4. Using supplied Allen wrench, open unit by removing bottom screw. Open cover & hang unit on top mounting screw.
5. Mark bottom hole using hang hole in back panel, remove unit, & drill bottom mounting hole using 3/16" drill bit. Insert supplied anchor into hole.
6. Hang unit on top mounting screw & align with bottom mounting hole. Insert supplied screw into anchor & securely tighten.
7. Insert 2 AA batteries.

### DEODORIZING ELEMENT INSTRUCTIONS

1. Open protective bag containing EZ-Disk by tearing at notch. Gently press EZ-Disk down & back into slot(s) to prevent element interference with fan.
2. Install 1-5 EZ-Disks depending on your cubic footage needs. Each EZ-Disk treats 2,000 ft<sup>3</sup>.
3. Ensure slide switch is turned ON & adjusted to desired setting. Use setting 1 when maximum dry vapor output is required.
4. Close lid & reinsert bottom screw using Allen wrench.
5. Wash hands with soap & water to remove any residue from handling EZ-Disks.

**0** - OFF  
**Setting 1** - One minute ON, 5 minutes OFF  
**Setting 2** - One minute ON, 10 minutes OFF  
**Setting 3** - One minute ON, 15 minutes OFF



### IMPORTANT

1. Vaportek products use natural essential oils. If an allergic reaction occurs, please discontinue use immediately.
2. Do not allow EZ-Disk to contact surfaces other than the housing as contact may damage finished surfaces.
3. Ideal dry vapor release occurs at 50-80°F (10-27°C).
4. Replace EZ-Disks after 30 days of use.
5. Keep out of reach of children.

### SPECIFICATIONS

1. Blinking green LED operation indicator; blinking red when battery change is required. Unit will blink red a minimum of 72 hours before it stops operating.
2. Tamper resistant.
3. Approx. Dimensions: 7"H x 3"W x 3"L.
4. Weighs less than one pound.
5. Uses 2 AA batteries; batteries last for a minimum of 30 days at the highest setting.

### ONE YEAR LIMITED WARRANTY

Vaportek warrants this unit to be free from defects in workmanship and materials, under normal use and service, for one year from date of purchase by the original purchaser. If, at any time during the warranty period, the product is found to be defective or malfunctions, Vaportek will either repair or replace the defective part(s) at its discretion. Warranty does not apply if it is shown by Vaportek that the defect or malfunction was caused by unauthorized modifications, neglect, or abuse by the consumer. Further, any costs incurred by consumer due to unauthorized changes made to the product will not be covered by Vaportek. This warranty does not cover any other charges incurred by the consumer. Vaportek's sole responsibility is to repair or replace products within the terms stated above. This warranty applies only to products sold and used in the United States and Canada. Goods submitted for repair under this warranty must be sent freight prepaid to Vaportek, Inc. Call first for a return authorization number.

For service advice, contact your dealer or Vaportek.



P: 800.237.6367 | F: 262.246.5065  
www.vaportek.com | info@vaportek.com

#50-1228

Proudly made in the USA

Rev. 3/19