

TECHNICAL DATA

VAPOR SHARK® INDUSTRIAL ODOR-NEUTRALIZING SYSTEM

The Superior Alternative to Ozone Generators



Handle for easy transport

Heavy-duty dual hasps with locking capability

53 CFM blower 0.29/0.30 Amps | 30W | 120V 49 CFM blower 16W | 230V | 50/60Hz

Membrane rack

LEFT SIDE VIEW



RIGHT SIDE VIEW



Air inlet
Adjustable vent



WORKS FAST: Odor neutralizer is immediate & permanent.

ECONOMICAL: Membranes last for multiple jobs.

EASY TO USE: Just place membranes in the tray, insert into the machine, and turn on.

SUGGESTED APPLICATIONS

- Fire/Flood Damage Restoration
- Hydroponic & Grow Rooms
- Contents Restoration
- Manufacturing & Industrial Settings
- Real Estate/Foreclosures
- Crime Scene/Bioremediation
- Disaster Recovery
- Animal & Veterinary Facilities







TECHNICAL DATA

VAPOR SHARK® INDUSTRIAL ODOR-NEUTRALIZING SYSTEM

The Superior Alternative to Ozone Generators

PURPOSE

- Industrial strength, portable odor neutralizing system.
- Treats areas up to 50,000 ft³ (10,000 ft³ per membrane).
- Effective against intense organic odors caused by fires, floods, hoarding, animals, sewage, crime scenes, and others.
- · Penetrating dry vapor treats atmosphere, structure, and contents simultaneously.



- Place on firm, stable surface, preferably in a relatively high location.
- Situate the unit so air flow at both ends is unobstructed.
- For initial air treatment, open air inlet a half-inch. After 10-15 minutes, adjust air inlet as necessary to reduce or increase output.
- Light contamination may require as little as 15-60 minutes.
- Severe contamination may require several hours or days.
- Do not locate or use near water.

IMPORTANT INFORMATION

- No evacuation or recovery period is required with Vaportek technology.
- Not designed for continuous, long-term operation.
- Membrane life is approximately 270 hours.
- To extend membrane life, close air inlet opening and front access door in between treatments.
- Store membranes in a cool, dry place and keep away from extreme heat.

· Vaportek products use natural essential oils. If an allergic reaction occurs, discontinue use immediately.

- Dimensions: 14"H x 8"W x 17"L.
- · Weight: 10 lbs.
- · Five-year limited warranty.

safe, effective alternative to ozone. It is not recommended for use with ozonegenerating equipment, but may be used after ozone treatment to eliminate residual ozone related odors.

IMPORTANT: This system provides a

REORDER INFORMATION:

UNIT ONLY:

Vapor Shark (#90-0950)


VAPOR SHARK MEMBRANES:

Five-Pack/3X Industrial (#90-0953/5) Five-Pack/Lemon* (#90-0953-05/5)

Five-Pack/S.O.S. (#90-0953-85/5)



* Lemon membranes are recommended for use with 3X Industrial membranes for odor control with a lighter scent. Because Lemon does not contain the same odor neutralizing







Membranes

Solution),

and Lemon

available in 3X

Industrial, S.O.S. (Smoke Odor